

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
15 November 2001 (15.11.2001)

PCT

(10) International Publication Number
WO 01/85526 A1

(51) International Patent Classification⁷: B62B 13/08

(74) Agents: TAKEDA, Masahiko et al.; Zexel Bldg.
Akasaka, 13-1, Nagata-cho 2-chome, Chiyoda-ku, Tokyo
100-0014 (JP).

(21) International Application Number: PCT/JP01/03933

(22) International Filing Date: 11 May 2001 (11.05.2001)

(81) Designated States (*national*): AT, AU, BG, CA, CH, CZ,
DE, DK, EE, ES, FI, GB, HU, IS, JP, KP, LT, LU, LV, MA,
MN, NO, NZ, PL, PT, RO, RU, SE, TR, UA, US, VN, YU.

(25) Filing Language: English

(26) Publication Language: English

(84) Designated States (*regional*): Eurasian patent (AM, AZ,
BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

(30) Priority Data:
00 1 08373.2 12 May 2000 (12.05.2000) CN

Published:


- with international search report
- before the expiration of the time limit for amending the
claims and to be republished in the event of receipt of
amendments

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): TAKAHASHI, Tetsu
[JP/JP]; 14-15, Akiya 2-chome, Yokosuka-shi, Kana-
gawa-ken 240-0105 (JP).

For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.

(54) Title: SLIDING DEVICE FOR SNOW SPORTS



(57) Abstract: The sliding device for snow in accordance with the present invention is provided with a supporting slide (1) and a turning slide (2) arranged in front of the supporting slide. The smallest portion of said turning slide (2) is wider than the widest portion of the supporting slide (1). The ground contact portion (2a) of said turning slide spreads out forward and is essentially a trapezoid-like plate. The largest width of this ground contact portion is about 1.01 ~ 1.1 times the smallest width of the ground contact portion.

WO 01/85526 A1

DESCRIPTION

Sliding device for snow sports

FIELD OF THE INVENTION

5

The present invention relates to a sliding device for snow sports according to the preamble of claim 1.

BACKGROUND OF THE INVENTION

10

Such a sliding device is disclosed in US 5,351,975, wherein the turning slide is round-shaped and the supporting slide is essentially a rectangular plate having a rounded front end. A stabilizing bar is provided between a sleeve in which the fork is rotatable and the front end of the supporting slide, so that this stabilizing bar is positioned before the rider's feet, which are to be positioned on a supporting plate provided on the supporting slide.

20

Such a sliding device presents some problems. Since the front portion of the turning slide is round-shaped, the sliding device cannot move in a straight line properly. While the sliding device moves forward in curves, the length of the edge of the turning slide in contact with the snow is relatively short; therefore, the edge effect does not function well and changing direction is difficult.

25

SUMMARY OF THE INVENTION

30

It is an object of the present invention to provide a sliding device in such a way that the device is capable

of moving in a straight line properly, whereas it is easy to perform curves when riding on the sliding device.

It is a further object to improve the stability of the device.

BRIEF DESCRIPTION OF THE DRAWINGS

The objects, details, advantages and the further features of the present invention will become apparent from the following description and claims in conjunction with the drawings, which show an example of a sliding device according to the present invention.

Fig. 1 is a perspective view of the sliding device according to the invention;

Fig. 2 is a top view of the sliding device in Fig. 1;

Fig. 3 is a perspective view of the connector for the foot strap on the sliding device in Fig. 1;

Fig. 4 is a side plan view in partial section of a quick release system;

Fig. 5 is a top view of the supporting plate of the quick release system; and

Fig. 6 shows schematically a side view of a hinge on the supporting plate.

DETAILED DESCRIPTION OF THE INVENTION

The total length of the sliding device for an adult rider in accordance with the present invention is about 1.5 m. The sliding device comprises a supporting slide 1 and a turning slide 2, wherein the turning slide 2 is arranged

in front of the supporting slide 1. The turning slide 2 is connected with the supporting slide 1 by means of a front fork 3 extending from the lower portion of a rotating arm 4. The rotating arm 4 can freely rotate in a sleeve 5 of a frame comprising two rigid struts 6 and a stabilizing bar 10. The sleeve 5 is inclined in relation to the ground and the angle of the inclination can be, for example, 65°. The two rigid struts 6 are welded to the lower portion of said sleeve 5 and can be made of metal tubes. The tubular struts 6 extend downwardly from the front ends and continuously spread outward, until they reach the supporting slide 1. The struts 6 then continue as frame extensions 6a arranged longitudinally on the supporting slide 1. In the middle part of the supporting slide 1 the frame extensions are interrupted in such a way that a rear portion of the frame extensions 6a' can pivot around a hinge 9a or a flexible connection in relation to the front frame extensions 6a as shown by arrow X in Fig. 6.

Both frame extensions 6a and 6a' extend along the side edges of the upper surface of the supporting slide 1. The rear ends of the rear frame extensions 6a' are inclined upward after they diverge from the supporting slide 1. The rear frame extensions 6a' are connected to each other via a rounded rear portion 6a".

Between the tubular struts 6 of metal and the frame extensions 6a and 6a' on said supporting slide 1, a supporting plate 11 for placing the rider's feet is disposed. A rectangular rigid plate made of metal preferable forms the main body of the supporting plate 11.

The two lateral edges of the supporting plate 11 are preferably welded along their entire length to the inner sides of the frame extensions 6a and 6a'. Moreover, the supporting plate 11 for placing the rider's feet can be
5 attached to the supporting slide 1 by screws in at least four locations, the two lateral sides, the rear side and the front side, such that the supporting plate 11 and the supporting slide 1 are firmly connected to each other. This supporting plate 11 is divided by the hinge 9a or a
10 flexible connection into a front plate 11' and a rear plate 11", wherein the front plate 11' is firmly connected with the frame extensions 6a and the rear plate 11" is firmly connected with the rear frame extensions 6a'.

15 The tubular struts 6 and the supporting plate 11 are preferable welded together in advance, and the combination is then attached to the supporting slide 1 by screws. The supporting plate 11 is preferably covered with non-skid material, such as rubber, on the surface which is in
20 contact with the rider's feet.

On the front supporting plate 11', a slipper-like foot strap 12 is attached to the frame extensions 6a. The foot strap 12 can loosely keep rider's two feet side by side,
25 in the longitudinal or lateral direction on the supporting plate 11. The foot strap 12, as shown in Fig. 3, can be adjusted back and forth on the frame extensions 6a by fasteners 122 previously mounted at the two sides of the frame extensions 6a. In addition, the foot strap 12 can
30 be formed from a shape memory alloy and is provided with an adjustment means 121 to change the size of the foot strap 12 to accommodate the size of a specific rider's

feet. Thus, the position of the rider on the sliding device is capable of being properly adjusted to depend on the desire or body build of the rider by adjusting the length of the foot strap 12.

5

The upper portion of the sleeve 5 is attached to the stabilizing bar 10 formed from a metal tube. The front end of the bar 10 is connected to the sleeve 5, and the bar 10 then extends downwardly and rearwardly to the rear supporting plate 11". A shock absorber 101 is mounted near the central portion of the bar 10, so that the bar 10 is divided by the shock absorber into a front portion 10 and a rear portion 10'. The rear end of the rear portion 10' is attached to the rear supporting plate 11" or at the supporting slide 1 by means of a pivot in the form of a bracket 9 or the like. Said shock absorber 101 can be made of rubber, be hydraulic or be an MCU type. In addition, to prevent the shock absorber 101 from moving up and down or back and forth, a tube covers the entire shock absorber 101. The tube is used to guide the shock absorber 101 and connect the shock absorber 101 to the rear portion 10' of the bar and to the rear supporting plate 11", where the bracket 9 or the like is mounted.

25 Further, a spring can be provided for the shock absorber, which spring is positioned between the front portion 10 of the bar and the rear portion 10', wherein both portions 10 and 10' are guided in the form of a spring biased telescope.

30

Fig. 6 shows schematically the hinge 9a between front and rear portions 11' and 11" of the supporting plate 11.

These front and rear portions 11' and 11" are firmly connected with the frame extensions 6a and 6a' respectively, which are separated from each other so that the supporting slide 1 can be bent around the axis of the hinge 9a or flexible connection when riding on the sliding device as shown by arrow X.

Instead of a hinge 9a between front and rear portion 11' and 11" of the supporting plate 11, a flexible connection can also be provided between these two portions. Such a flexible connection can also be provided between the frame extensions 6a and 6a'.

As described previously, the entire length of the sliding device is 150 cm, and the length of the supporting slide 1 is about 95 cm. The front fifth of the supporting slide 1 is curved up until the height of the front end is about 10 cm. Moreover, the rear end of the supporting slide 1 is likewise curved up until its height is about 1 cm. With the configuration described above, the main portion of the supporting slide 1 is a substantially rectangular ground contact portion 1a and the width of the curved front portion of the supporting slide 1 is gradually narrowed toward the front end.

25

With reference to Fig. 2, said ground contact portion 1a of the supporting slide 1 is widest at c near the front end. For example, when the total length of the supporting slide 1 is about 95 cm, the width at c is preferred to be 22 cm. The width of the ground contact portion 1a becomes smaller from c to the smallest width at e, where the width is approximately 20 cm. The width again becomes larger

30

after e until the rear portion d, and the width after d is constant at approximately 21.5 cm. That is, the supporting slide 1 is not a parallelogram, and its width is smallest at the rear portion at e in the area of the rear supporting plate 11" or behind the hinge 9a.

With reference to Figs. 1 and 2, the front portion and the rear portion of said turning slide 2 are preferred to be curved up, like the supporting slide 1, and the main portion at the center of the turning slide 2 is the ground contact portion 2a. The total length of the turning slide 2 is preferred to be approximately 53 cm when the total length of the supporting slide 1 is 95 cm. Preferably, the height of the front end of the turning slide 2 is approximately 5 cm, and the height of the rear end is approximately 1 cm. The ground contact portion 2a of the turning slide 2 is not a parallelogram with a smallest width of approximately 26 cm at a on the rear end. The width of the turning slide 2 becomes larger toward the front, until the largest width of about 27 cm, at b on the front end of the ground contact portion 2a. Namely, the ground contact portion 2a of the turning slide 2 is a trapezoid-like plate, which is gradually wider toward the front. As described above, the smallest portion of the turning slide 2 is wider than the widest portion c of the supporting slide 1.

Specifically because of the shape of the ground contact portion 2a of the turning slide 2, curves are made more efficiently with the sliding device. When making a curve, the handlebar is turned left or right and the respective left edge or the right edge of the turning slide 2 can

instantly act on the ground. The sliding device can thus immediately and efficiently perform the desired curve. From various kinds of testing, good results can be achieved by setting the largest width (the width of the front end at b) of the ground contact portion 2a to be
5 approximately 1.01 ~ 1.1 times the smallest width (the width of the rear end at a) of the ground contact portion 2a.

10 The maintenance, movement and storage of the sliding device are achieved by means of a quick release system 14. The conveniently assembled or disassembled quick release system 14 is fastened at the lower end of the front fork 3. With reference to Figs. 1, 4 and 5, the quick-release
15 system 14 comprises a supporting plate 141 firmly connected with the fork and fastening elements 143, 144 provided on the turning slide 2. Position guide posts 142 for positioning the fork 3 are provided on the turning slide 2 and are inserted in the rounded-contoured supporting plate 141 through positioning holes 145 (Fig.
20 5). The position guide posts 142 can be embodied as screws inserted into the upper surface of the turning slide 2. Additionally screws can be used for fastening the guide posts on the supporting plate 141. The quick release system comprises an L-shaped lip 143 and a locking clamp
25 144, which are fastened on the turning slide 2 by means of screws. When connecting the quick release system 14 to the turning slide 2, first insert the front edge of the supporting plate 141 under the lip 143, then insert the position guide posts 142 into the positioning holes 154
30 and clamp the rear edge of the supporting plate 141 with the locking clamp 144. Said supporting plate 141 has

rounded contours, such that the stresses on the supporting slide 2 generated from jumps or special sliding stunts can be diverted. Thus the turning slide 2 is provided with a high efficiency support to prevent the slide from breaking.

5

Such a quick release system can also be provided between supporting slide 1 and frame extensions 6a and 6a' or the supporting plate 11 respectively.

10 The foremost end of the supporting slide 1 overlaps the rearmost end of the turning slide 2 by being separated from each other in the vertical direction. The overlap length of the slides is preferred to be about 5 cm. Although not shown in the figures, a shaft is fitted in
15 the upper end of said rotating arm 4, and the shaft can slide in the rotating arm 4. Consequently, the height of the rotating arm is adjustable. An adjustable head connector 18 protruding forward is mounted at the upper end of the rotating arm 4. The head connector 18 holds
20 the handlebar 19 at the central portion of the handlebar 19, wherein the length of the handlebar 19 is approximately 70 cm. The handlebar 19 is provided with grips 20, 21 at the lateral sides, such that the rider can hold the grips 20, 21 and thereby control the sliding
25 device. A stabilizer bar 22 is attached between the grips 20, 21 to enhance the strength of the handlebar 19. The longitudinal location of the grips 20, 21 is preferred to be between the front end of the supporting slide 1 and the rear end of the turning slide 2 when the turning slide 2
30 is aligned with the supporting slide 1.

When riding on the sliding device, the stabilizing bar 10 can be used to assist in performing curves by squeezing the bar 10 tightly between the rider's legs, wherein the rider can easily lean his weight to the edge of the turning side when making a curve. To perform such weight transformation efficiently, it is preferable to fasten the entire supporting plate 11 to the supporting slide 1 as firmly as possible, also in case of quick release system.

10 The supporting slide 1 and the turning slide 2 are both made from known laminated material of synthetic resin for snow boards or skis, such as wood, metal, glass fiber, carbon fiber, etc. The bottom edges of the slides are preferably enhanced with a sharp metal runner to protect the surface of the slides from the friction between the slides and the icy ground, especially from the friction generated during a sliding turn, and the so-called edge status when making a sliding turn.

20 The sliding device in accordance with the present invention, especially the structure of the turning slide described above, the sliding runner of the supporting slide 1 is always coincident with that of the turning slide 2 when sliding, even when the turning slide 2 is turned by the handlebar 19. Therefore, a ride can perform the sliding turn properly.

30 With the sliding device described above, even on soft powder snow ground or when the rider performs jumps or special sliding feats, it is possible to perform the sliding in a stable and smooth manner.

The dimensions of the components shown in the embodiments are generally for adult riders. However, if the riders are children, the dimensions can be changed accordingly.

Claims

1. A sliding device for snow sports comprising
a foot supporting slide (1) and a turning slide (2)
5 which are connected with each other by means of a
frame (5, 6, 10) and a rotating arm (4) guided in a
sleeve (5) of the frame,
wherein struts (6) and a stabilizing bar (10) are
provided between the sleeve (5) and a supporting
10 plate (11) on the supporting slide (1),
characterized in that
the supporting plate (11) is provided with a flexible
portion or hinge (9a) to allow a pivot movement
between a front portion (11') and a rear portion
15 (11'') of the supporting plate (11).
2. The sliding device according to claim 1, wherein the
stabilizing bar (10) is pivotably connected with the
rear portion (11'') of the supporting plate (11) and
20 is provided with a shock absorber (101).
3. The sliding device according to claims 1 and 2,
wherein frame extensions (6a) extend along the sides
of the supporting plate (11) and are divided into a
25 front portion (6a) and a rear portion (6a') in the
area of the hinge (9a) or flexible portion.
4. A sliding device for snow sports comprising
a supporting slide (1) and a turning slide (2) which
30 are connected with each other by means of a frame (5,
6, 10) and a rotating arm (4) guided in a sleeve (5)
of the frame,

wherein struts (6) and a stabilizing bar (10) are provided between the sleeve (5) and a supporting plate (11) on the supporting slide (1),
characterized in that

5 the smallest portion (a) of the turning slide (2) is wider than the widest portion (c) of the supporting slide (1), and a ground contact portion (2a) of said turning slide (2) spreads out forward and is substantially a trapezoid-like plate, the largest
10 width (b) of this ground contact portion (2a) being approximately 1.01 ~ 1.1 times the smallest width (a) of the ground contact portion.

5. The sliding device according to the preceding claims,
15 wherein said two frame extensions (6a) extend longitudinally along the lateral sides of the supporting slide (1), said foot supporting plate (11) is substantially formed of rigid material and is connected to said frame extensions (6a, 6a') by
20 welding the entire length of the lateral sides of the supporting plate to the frame extensions.

6. The sliding device according to claim 2, wherein the
25 shock absorber (101) is made of rubber, constituted hydraulically or is an MCU type, and is mounted in the central portion of said stabilizing bar (10).

7. The sliding device according to the preceding claims,
30 wherein at the front portion (11') of said supporting plate (11), a slipper-like foot strap (12) is mounted on said frame extensions (6a), and said foot strap can loosely keep rider's two feet side by

side, in the longitudinal or lateral direction on the supporting plate.

- 5 8. The sliding device according to claim 7, wherein said foot strap (12) is formed from shape memory alloy and is provided with an adjustment means (121) to accommodate the size of different riders' feet.
- 10 9. The sliding device according to the preceding claims, wherein the lower end of a fork (3) is connected to said turning slide (2) at a position on said turning slide about one fourth of the entire length of the turning slide (2) from the rear end of the turning slide by means of a quick release system (14).
- 15 10. The sliding device according to the preceding claims, wherein the supporting slide (1) is connected with the frame extensions (6a, 6a') or with the supporting plate (11) via a quick release system.

1/5




FIG. 1

2/5




FIG. 2

3/5




FIG. 3




FIG. 4

4/5




FIG. 5

5/5




FIG. 6

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 01/03933

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 B62B13/08

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B62B B62K

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 5 351 975 A (PETOUD FRANK) 4 October 1994 (1994-10-04) cited in the application figure 2	1
X	column 3, line 21 - line 28 column 3, line 33 - line 38	4,5,7
P,A	DE 200 18 795 U (WANG LEAO) 11 January 2001 (2001-01-11) page 2, line 17 - last line figure	1
A	WO 99 00290 A (OUBOTER WIM A) 7 January 1999 (1999-01-07) figure 1	1
	--- -/- ---	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

18 September 2001

Date of mailing of the international search report

25/09/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Cauderlier, F

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 01/03933

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
P, A	DE 200 14 985 U (HO SHENG CHIN) 23 November 2000 (2000-11-23) the whole document -----	9

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 01/03933

Patent document cited in search report		Publication date		Patent family member(s)	Publication date
US 5351975	A	04-10-1994	FR	2659864 A1	27-09-1991
			WO	9114608 A1	03-10-1991
DE 20018795	U	11-01-2001	DE	20018795 U1	11-01-2001
WO 9900290	A	07-01-1999	AU	7423498 A	19-01-1999
			WO	9900290 A1	07-01-1999
DE 20014985	U	23-11-2000	DE	20014985 U1	23-11-2000